

# MAKE UP LIGHTING -LINEAR

## LIGHTING SERIES

# NGA

### SPECIFICATION

- Composition: 100 % polyester (recycled PET appx. 50 %)
- Material Weight: 1300g /m<sup>2</sup> (+/- 5 %)
- Material Thickness: 6mm Natural & Mandarin colors (+/- 10 %)
- Product Weight:
  - Linear Lighting - Suspended: 4,370 kg / per pcs. (+/- 5 %)
  - Linear Lighting - Surface Mounted: 4,420 kg / per pcs. (+/- 5 %)
  - Linear Lighting - Surface Mounted: 6,185 kg / per pcs. (+/- 5 %)

### PERFORMANCE

- Fire Rates: B, S1, d0 (EN-13501)
- Light fastness: 6+ (ISO-105 B02)
- Health : 99.9 % Antibacterial (ISO-20743)
- Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thermal insulating: 0,040 W/mK
- Abrasion: EN ISO 12947 / Performance 'A'

### KEY FEATURES & BENEFITS

- Available in 7 Natural colors & 34 Mandarin colors.
- Highly durable providing long-term stability and performance.
- Safe, non-toxic, non-irritant & without red list chemical binders.
- Recycled and recyclable.
- 10 years warranty.

### CARE

- Easy to clean with a damp cloth or vacuum cleaner.
- Indoor use only.

### INSTALLATION

- Designed for easy assembly with aluminium pipe system fitted to an aluminium base.

### DIMENSIONS (MM):

MU400	MU401	MU420
W: 1800mm	W: 1800mm	Lighting
L: 260mm	L: 260mm	W: 1800mm
D: 90mm	D: 90mm	L: 260mm
		D: 90mm
		Wing
		W: 1800mm
		L: 260mm
		D: 40mm



Linear Lighting - Suspended MU400



Linear Lighting - Surface Mounted MU401



Linear Lighting - Surface Mounted MU420

Linear Lighting Light Source Specification	
Wattage	33W
Input Voltage	220 - 240V AC
Input Frequency	50 / 60 Hz
Lumen output	3135 lm
*** Colour Temperature	2700K, 3000K, 4000K options
Colour Rendering Index	standard 80CRI or optional 90CRI
Unified Glare Rating	UGR<19
Dimmable	DALI, Push Dim, Bluetooth, Phase Cut options
Lighting Type	Direct Lighting

\*\*\* Please check lighting control switch options on page 2.

\*\*\* Lighting source standard diffuser is Micro Prismatic.

\*\*\* Colour temperatures of lighting sources can be customised.

## MAKE UP LIGHTING - LINEAR AND SPOT

### SPECIFICATION

- Composition: 100 % polyester (recycled PET appx. 50 %) MU410 L: 1800mm
- Material Weight: 1300g /m<sup>2</sup> (+/- 5 %) W: 260mm
- Material Thickness: 6mm Natural & Mandarin colors (+/- 10 %)D: 90mm
- Product Weight: Linear Lighting - Suspended: 5,710 kg / per pcs. (+/- 5 %)
  - Linear + Spot Lighting - Surface Mounted: 5,760 kg / per pcs. (+/- 5 %)
  - Linear + Spot Lighting - Surface Mounted: 7,525 kg / per pcs. (+/- 5 %)

### DIMENSIONS (MM):

MU411	MU430
L: 1800mm	Lighting
W: 260mm	L: 1800mm
D: 90mm	W: 260mm
	D: 90mm
	Wing
	L: 1800mm
	W: 260mm
	D: 40mm

### PERFORMANCE

- Fire Rates: B, S1, d0 (EN-13501)
- Light fastness: 6+ (ISO-105 B02)
- Health : 99.9 % Antibacterial (ISO-20743)
- Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thermal insulating: 0,040 W/mK
- Abrasion: EN ISO 12947 / Performance 'A'

### KEY FEATURES & BENEFITS

- Available in 7 Natural colors & 34 Mandarin colors.
- Highly durable providing long-term stability and performance.
- Safe, non-toxic, non-irritant & without red list chemical binders.
- Recycled and recyclable.
- 10 years warranty.

### CARE

- Easy to clean with a damp cloth or vacuum cleaner.
- Indoor use only.

### INSTALLATION

- Designed for easy assembly with aluminium pipe system fitted to an aluminium base.



Linear + Spot Lighting -  
Suspended MU410



Linear + Spot Lighting - Surface  
Mounted MU411



Linear + Spot Lighting - Surface  
Mounted MU430

\*\*\* Please check lighting control switch options on page 2.  
 \*\*\* Lighting source standard diffuser is Micro Prismatic.  
 \*\*\* Colour temperatures of lighting sources can be customised.

Linear + Spot Lighting Light Source Specification	
Wattage	25W
Input Voltage	220 - 240V AC
Input Frequency	50 / 60 Hz
Lumen output	2500 lm
*** Colour Temperature	2700K, 3000K, 4000K options
Colour Rendering Index	standard 80CRI or optional 90CRI
Unified Glare Rating	NO UGR
Dimmable	DALI, Push Dim, Bluetooth, Phase Cut
Lighting Type	options Direct Lighting