

SPECIFICATION

- Composition: 100 % polyester (recycled PET appx. 50 %)
- Material Weight: 1300g /m² (+/- 5 %)
- Material Thickness: 6mm Natural & Mandarin colors (+/- 10 %)
- Product Weight: 90cm / Natural: kg per pcs. (+/- %5)
90cm / Mandarin: kg per pcs. (+/- %5)
115cm / Natural: kg per pcs. (+/- %5)
115cm / Mandarin: kg per pcs. (+/- %5)

PERFORMANCE

- Fire Rates: B, S1, d0 (EN-13501)
- Light fastness: 6+ (ISO-105 B02)
- Health : 99.9 % Antibacterial (ISO-20743)
- Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thermal insulating: 0,040 W/mK
- Abrasion: EN ISO 12947 / Performance 'A'

KEY FEATURES & BENEFITS

- Available in 7 Natural colors & 34 Mandarin colors.
- Highly durable providing long-term stability and performance.
- Safe, non-toxic, non-irritant & without red list chemical binders.
- Recycled and recyclable.
- 10 years warranty.

CARE

- Easy to clean with a damp cloth or vacuum cleaner.
- Indoor use only.

INSTALLATION

- Designed for easy assembly with adjustable ceiling mount units.

DIMENSIONS (MM):

SP205	SP207
Ø: 900mm	Ø: 1150mm
H: 200mm	H: 240mm
Lighting Fixture: Ø: 220mm	Lighting Fixture: Ø: 240mm



Suspended Wire / Ambiance Lighting

SP206	SP208
Ø: 900mm	Ø: 1150mm
H: 200mm	H: 240mm
Lighting Fixture: Ø: 220mm	Lighting Fixture: Ø: 240mm



Suspended Wire / Task Lighting

Light Source Specification	
Wattage	25W
Input Voltage	220 - 240V
Input Frequency	50 / 60 Hz
Lumen output	2500 lm
*** Color Temperature	2700K, 3000K, 4000K options
Color Rendering Index	90CRI
Unified Glare Rating	UGR<19
Dimmable	On/Off, DALI, Push Dim, Bluetooth, Phase Cut
Lighting Type	Direct Lighting

Ripple wall lamps are available with Mandarin colors at outer surface. Colour temperatures of lighting sources can be customised.