FLOW

T-GRID CEILING TILE SERIES



Unique, quirky and dramatic. 14six8 T-grid ceiling tiles, or drop ceiling tiles as they are also known, offer the unmistakable contradiction to the antiquated plain grid ceiling tiles available and our acoustic ceiling tiles are in PET material for excellent acoustic performance.

The majority of our standard 600mm X 600mm (actual size 598mm) tiles can be arranged in unison with one another or by simply rotating every other tile by 90 degrees which can deliver a completely different visual impression.

Each designed with 3 dimensional suspended elements, our ceiling tiles create the perfect sound trap that will not only look amazing, but will also have superior acoustic performance.

SPECIFICATION

- Composition: 100 % polyester (recycled PET appx. 50 %)
- Material Weight: 12mm: 2600g/m² (+/- 5%)
- Material Thickness: 12mm (+/- 10 %)

PERFORMANCE

- Acoustic NRC Rating: E87 NRC 0.75 (12mm material)
- Fire Rates: B, S1, d0 (EN-13501 1:2018)
- Light fastness: 6+ (ISO-105 B02)
- Health: 99.9 % Antibacterial (ISO-20743)
- Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thermal insulating: 0,040 W/mK
- Abrasion: EN ISO 12947 / Performance 'A'

KEY FEATURES & BENEFITS

- Available in 19 colours.
- Highly durable providing long-term stability and performance.
- Safe, non-toxic, non-irritant & without red list chemical binders.
- Recycled and recyclable.

CARE

- Easy to clean with a damp cloth or vacuum cleaner.
- Indoor use only.

INSTALLATION

• T-Grid ceiling tiles are designed to sit within a 600 x 600 ceiling grid.

DIMENSIONS (MM):





