

PEBBLE

TILE SERIES

NGA


SPECIFICATION

- Composition: 100 % polyester (recycled PET appx. 50 %)
- Material Weight: 6mm: 1300g/m² (+/- 5%)
12mm: 2600g/m² (+/- 5%)
- Material Thickness: 6mm / 12mm Natural & Mandarin colors (+/- 10 %)
- Product Weight:


6mm / Natural / Pebble per pcs. (+/- %5)	12mm / Natural / Pebble per pcs. (+/- %5)
XL: 2,10 kg	XL: 4,10 kg
L: 0,95 kg	L: 2,05 kg
M: 0,50 kg	M: 1,25 kg
S: 0,50 kg	S: 0,82 kg
XS: 0,35 kg	XS: 0,68 kg
6mm / Mandarin / Pebble	12mm / Mandarin / Pebble
XL: kg	XL: kg
L: kg	L: kg
M: kg	M: kg
S: kg	S: kg
XS: kg	XS: kg

DIMENSIONS (MM):


TLS668
r: 550mm
Ø: 1100mm




TLS666
r: 390mm
Ø: 780mm




TLS664
r: 290mm
Ø: 580mm



TLS664
r: 300mm
Ø: 600mm



TLS660
r: 250mm
Ø: 500mm



PERFORMANCE

- Acoustic Rates: 6mm Natural: NRC (EN-11654)
6mm Mandarin: 0.25 NRC (EN-11654)
6mm Natural + Feltfill: NRC (EN-11654)
6mm Mandarin + Feltfill: 0.95 NRC (EN-11654)
12mm Natural: 0.40 NRC (EN-11654)
12mm Mandarin: NRC (EN-11654)
12mm Natural + Feltfill: 1.00 NRC (EN-11654)
12mm Mandarin + Feltfill: NRC (EN-11654)
- Fire Rates: B, S1, d0 (EN-13501)
- Light fastness: 6+ (ISO-105 B02)
- Health : 99.9 % Antibacterial (ISO-20743)
- Formaldehyde-free (ISO-14184)
- Moisture Absorption: >0.03 % by weight (50°C/122°F at 90% relative humidity)
- Thermal insulating: 0,040 W/mK
- Abrasion: EN ISO 12947 / Performance 'A'

KEY FEATURES & BENEFITS

- Available in 7 Natural colours & 33 Mandarin colours.
- Highly durable providing long-term stability and performance.
- Safe, non-toxic, non-irritant & without red list chemical binders.
- Recycled and recyclable.

CARE

- Easy to clean with a damp cloth or vacuum cleaner.
- Indoor use only.

INSTALLATION

- Prior to installation, walls and surfaces must be clean, dust-free and void of any defects or imperfections. Contact-type adhesive for applying plate on surfaces such as plasterboard, concrete, block, plywood, MDF and particleboard. NGA recommends Pattex PL600 & Liquid Nails LN-2000 or equivalent adhesive with a glue gun.

