

# FUSION FLEX 28.8W/M

NGA/LL/HP/1/120/28.8/XXXX/IP

LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION



Fusion Flex 28.8w per metre LED strip.

## PRODUCT NOTES

Fusion Flex LED strip is supplied in 5m reels with a 1m tail at each end as standard. NGA recommends all LED strip is used in conjunction with appropriate aluminium heat sink for heat dissipation. For a homogenous appearance, please select aluminium profile with a depth greater than the LED pitch. Custom cut LED fixtures are available upon request.

## PRODUCT CODE BUILDER

Please specify the appropriate colour temperature and IP rating with your enquiry. **E.g., NGA/LL/HP/1/120/28.8/3000/20**



## TECHNICAL INFORMATION

Product Code	NGA/LL/HP/1/120/28.8/XXXX/IP
Product Group	LED Strip
Power Consumption	28.8w/m
Supply Voltage	DC24V
LEDs per metre	120
Cutting Interval	50mm
LED Pitch	8.33mm
Cable Gauge	20 AWG

Height	1.3mm
Type	Constant Voltage
Efficacy	101lm/w (@ 3000k)
IP Rating Options	IP20 / IP66
CRI	Ra≥90
MacAdam Step	2SDCM
Control Gear	On/Off / Mains / 0-10 / DALI / DMX
Lifetime	50.000 hours at L80

Colour Temperature	2400k	2700k	3000k	4000k	6000k
Lumen Output	2736lm	2820lm	2910lm	3000lm	3078lm

IP Rating	IP20	IP65	IP66	IP67	IP68
Width	10mm	-	10mm	-	-

### HEAD OFFICE

T: +44 (0) 1276 686175 | E: [info@nogreyarea.co.uk](mailto:info@nogreyarea.co.uk)

### MENA REGION HQ

T: +971 (0) 433 38300 | E: [info@nogreyarea.me](mailto:info@nogreyarea.me) | [www.no-grey-area.com](http://www.no-grey-area.com)