FUSION FLEX 9.6W/M

NGA/LL/SP/1/120/9.6/3000/20

PRODUCT DESCRIPTION

Fusion Flex 9.6w per metre LED strip.

PRODUCT NOTES

Fusion Flex LED strip is supplied in 5m reels with a 1m tail at each end as standard. NGA recommends all LED strip is used in conjunction with appropriate aluminium heat sink for heat dissipation. For a homogenous appearance, please select aluminium profile with a depth greater than the LED pitch. Custom cut LED fixtures are available upon request.

PRODUCT CODE BUILDER

Please specify the appropriate colour temperature and IP rating with your enquiry. E.g., NGA/LL/SP/1/120/9.6/3000/20


















TECHNICAL INFORMATION

| Product Code | NGA/LL/SP/1/120/9.6/XXXX/IP |
|-------------------|-----------------------------|
| Product Group | LED Strip |
| Power Consumption | 9.6w/m |
| Supply Voltage | DC24V |
| LEDs per metre | 120 |
| Cutting Interval | 50mm |
| LED Pitch | 8.33mm |
| Cable Gauge | 22 AWG |

| Height | 1.7mm |
|--------------|------------------------------------|
| Туре | Constant Voltage |
| Efficacy | 101lm/w (@ 3000k) |
| IP Rating | IP20/IP66/IP67/IP68 |
| Options CRI | Ra≥90 |
| MacAdam Step | 2SDCM |
| Control Gear | On/Off / Mains / 0-10 / DALI / DMX |
| Lifetime | 50.000 hours at L80 |

| Colour Temperature | 2400k | 2700k | 3000k | 4000k | 6000k |
|--------------------|-------|-------|-------|--------|--------|
| Lumen Output | 912lm | 940lm | 970lm | 1000lm | 1026lm |
| | | | | | |

| IP Rating | IP20 | IP65 | IP66 | IP67 | IP68 |
|-----------|------|------|------|--------|--------|
| Width | 8mm | - | 8mm | 10.5mm | 10.5mm |

T +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

