

# FUSION FLEX DIM TO WARM 14W/M

NGA/LL/DTW/1/9696/14/30-18/IP

LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION

Fusion Flex Dim to Warm 14w per metre LED strip.


## PRODUCT NOTES

Fusion Flex LED strip is supplied in 5m reels with a 1m tail at each end as standard. NGA recommends all LED strip is used in conjunction with appropriate aluminium heat sink for heat dissipation. For a homogenous appearance, please select aluminium profile with a depth greater than the LED pitch. Custom cut LED fixtures are available upon request.



## PRODUCT CODE BUILDER

Please specify white colour temperature and the IP rating with your enquiry. E.g, NGA/LL/DTW/1/9696/14/30-18/68



## TECHNICAL INFORMATION

Product Code	NGA/LL/DTW/1/9696/14/30-18/IP
Product Group	LED Strip
Power Consumption	14w/m
Supply Voltage	DC24V
LEDs per metre	96+96
Cutting Interval	62.5mm
LED Pitch	10.4mm
Cable Gauge	22 AWG

Height	1.7mm
Type	Constant Voltage
Efficacy	75lm/w (@ 3000k)
IP Rating Options	IP20 / IP65 / IP66 / IP67 / IP68
CRI	Ra ≥ 90
MacAdam Step	2SDCM
Control Gear	Mains / 0-10 / DALI / DMX
Lifetime	50,000 hours at L80

Colour Temperature	-	-	3000k	-	--
Lumen Output	-	-	1050lm	-	

IP Rating	IP20	IP65	IP66	IP67	IP68
Width	10mm	-	10mm	12.5mm	12.5mm

### HEAD OFFICE

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

### MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

# NGA