FUSION NEON 1615V RGBW 15W/M IP68

NGA/LL/NF/1615/V/15/RGBW-27/68/CE

LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

Vertical bend 15w RGBW IP68 Fusion Neon

PRODUCT NOTES

Fusion Neon is typically supplied in custom cut lengths but is also available in 5m reels with a cable at each end.

The product is supplied with 5 mounting clips per metre as standard or is available with an aluminium mounting channel upon request.

The white chip is supplied as 2700K as standard however please contact a member of the team if other colour temperatures are required

PRODUCT CODE BUILDER

CE = Cable Entry

E.g., NGA/LL/NF/1615/V/15/RGBW-27/68/RE


















TECHNICAL DATA

Product Code	NGA/LL/NF/1615/V/15/RGBW-27/68/CE		
Light Fixture Type	Vertical Bending Fusion Neon		
Cable Entry	End / Rear / Side L / Side R		
Cutting Interval	71mm		
Dimensions	W:16 x H:15mm		
IP Rating	IP68		
Bending Diameter	300mm		
Efficacy	39lm/w (RGBW)		

Power	15w/m
IK Rating	IK08
SupplyVoltage	24V DC
CRI	≥90
Warranty	5 years (3 years when submerged)
MacAdam Step	2SDCM
Control Gear	0-10 / DALI / DMX
Mounting Clip Dims	15 x 18.2 x 10.1mm (L x W x H)

Colour Temperature	Red	Green	Blue	2700k	RGBW
Lumen Output	62lm	205lm	46lm	272lm	585lm

HEAD OFFICE

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk



CABLE ENTRY







Side Cable Entry (SE)




Rear Cable Entry (RE)

MOUNTING ACCESSORIES




Mounting Clips: 15x18.2x10.1mm



Aluminium Profile: 1000x18.6x17.8mm

UNREELING

When unreeling NGA's Neon Flex there must be at least 2 people working together. One holding / supporting the reel and the other pulling the neon out for installation. This can avoid twisting the internal LED and damaging it.



Distance <1.5m



Do not twist

