

FUSION NEON 3020V 19W/M IP67

NGA/LL/NF/3020/V/19/XXXX/67/CE

LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

Vertical bend 19w IP67 Fusion Neon

PRODUCT NOTES

Fusion Neon is typically supplied in custom cut lengths but is also available in 5m reels with a cable at each end.



The product is supplied with 5 mounting clips per metre as standard or is available with an aluminium mounting channel upon request.

PRODUCT CODE BUILDER

XXXX = Colour Temperature

CE = Cable Entry

E.g., NGA/LL/NF/3020/V/19/3000/67/RE



TECHNICAL DATA

Product Code	NGA/LL/NF/3020/V/19/XXXX/67/EE
Light Fixture Type	Vertical Bending Fusion Neon
Cable Entry	End Cable Entry only
Cutting Interval	50mm
Dimensions	W:30 x H:20mm
IP Rating	IP67
Bending Diameter	300mm
Efficacy	58lm/w (4000k)

Power	19w/m
IK Rating	N/A
Supply Voltage	24V DC
CRI	≥90
Warranty	5 years
MacAdam Step	2SDCM
Control Gear	On/Off / Mains / 0-10 / DALI / DMX
Mounting Clip Dims	20 x 33 x 20mm (L x W x H)

Colour Temperature	2700k	3000k	3500k	4000k	5500k
Lumen Output	1005lm	1073lm	1089lm	1053lm	1053lm

HEAD OFFICE

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA

CABLE ENTRY




End Cable Entry (EE)

MOUNTING ACCESSORIES




Mounting Clips: 20 x 33 x 20mm




Aluminium Profile: 1000 x 32 x 20mm

UNREELING

When unreeling NGA's Neon Flex there must be at least 2 people working together. One holding / supporting the reel and the other pulling the neon out for installation. This can avoid twisting the internal LED and damaging it.



Distance <math>< 1.5\text{m}</math>



Do not twist

HEAD OFFICE

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com