FUSION FLEX 19.2W/M MINI 3000K IP20

NGA/LL/SPM/1/280/19.2/3000/20

LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A Medium Output, High Performance LED Strip, with a sleek design for use in mini profiles.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.






















TECHNICAL INFORMATION

| Product Code | NGA/LL/SPM/1/280/19.2/3000/20 |
|--------------------|-------------------------------|
| Product Group | LED Strip |
| Power Consumption | 19.2w/m |
| Supply Voltage | 24V DC |
| Туре | Constant Voltage |
| Lumen Output | 1930 |
| Efficacy | 101lm/w |
| Colour Temperature | 3000K |
| CRI | Ra≥90 |
| MacAdam Step | <3SDCM |
| Lifetime | L80 50,000Hrs |

| LEDs Per Meter | 280 led/m |
|-----------------------|-----------------------------------|
| Cutting Interval | 25mm |
| LED Pitch | 3.57mm |
| Height | 1.2mm |
| Width | 4mm |
| Max Run Length | 5m |
| Control Gear | On/Off/ Mains / 0-10 / DALI / DMX |
| IP Rating | IP20 |
| Operating Temperature | -20 to 50°C |
| Beam Angle | 120° |
| Classification | 3 |

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

