

FUSION FLEX 28.8W/M 6000K IP20

NGA/LL/HP/1/120/28.8/6000/20


LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A High Output LED Strip, designed to provide high quality illumination for a range of applications.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.



TECHNICAL INFORMATION

Product Code	NGA/LL/HP/1/120/28.8/6000/20
Product Group	LED Strip
Power Consumption	28.8w/m
Supply Voltage	24V DC
Type	Constant Voltage
Lumen Output	2940
Efficacy	102lm/w
Colour Temperature	6000K
CRI	Ra≥90
MacAdam Step	<3SDCM
Lifetime	L80 50,000Hrs

LEDs Per Meter	120 led/m
Cutting Interval	50mm
LED Pitch	8.33mm
Height	14mm
Width	10mm
Max Run Length	3m
Control Gear	On/Off/ Mains / 0-10 / DALI / DMX
IP Rating	IP20
Operating Temperature	-25 to 60°C
Beam Angle	120°
Classification	3

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA