## **FUSION FLEX 38.4W/M 2400K IP20**

NGA/LL/HP/1/240/38.4/2400/20

LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A High Output LED Strip, designed to provide high quality illumination for a range of applications.

## PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.






















## TECHNICAL INFORMATION

Product Code	NGA/LL/HP/1/240/38.4/2400/20
Product Group	LED Strip
Power Consumption	38.4w/m
Supply Voltage	24V DC
Туре	Constant Voltage
Lumen Output	3094
Efficacy	80lm/w
Colour Temperature	2400K
CRI	Ra≥90
MacAdam Step	<3SDCM
Lifetime	L80 50,000Hrs

LEDs Per Meter	240 led/m
Cutting Interval	25mm
LED Pitch	4.2mm
Height	1.4mm
Width	12mm
Max Run Length	2m
Control Gear	On/Off/ Mains / 0-10 / DALI / DMX
IP Rating	IP20
Operating Temperature	-25 to 60°C
Beam Angle	120°
Classification	3

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

