

FUSION FLEX 4.8W/M - PINK IP68

NGA/LL/SP/1/60/4.8/PINK/68


LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A Low Output, Single Colour LED Strip, designed to add a vibrant touch to any setting.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.



TECHNICAL INFORMATION

Product Code	NGA/LL/SP/1/60/4.8/PINK/68
Product Group	LED Strip
Power Consumption	4.8w/m
Supply Voltage	24V DC
Type	Constant Voltage
Lumen Output	336
Efficacy	70lm/w
Colour Temperature	PINK
CRI	N/A
MacAdam Step	N/A
Lifetime	L80 50,000Hrs

LEDs Per Meter	60 led/m
Cutting Interval	100mm
LED Pitch	16.67mm
Height	4.5mm
Width	10mm
Max Run Length	10m
Control Gear	On/Off/ Mains / 0-10 / DALI / DMX
IP Rating	IP68
Operating Temperature	-25 to 60°C
Beam Angle	120°
Classification	3

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA