

FUSION FLEX 9.6W/M 80LED/M HE 2400K IP65

NGA/LL/SP/1/80/9.6/2400/65/HE


LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A Low Output, High Efficiency LED Strip, designed to provide exceptional lighting performance with energy saving benefits.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.



TECHNICAL INFORMATION

| | |
|--------------------|-------------------------------|
| Product Code | NGA/LL/SP/1/80/9.6/2400/65/HE |
| Product Group | LED Strip |
| Power Consumption | 9.6w/m |
| Supply Voltage | 24V DC |
| Type | Constant Voltage |
| Lumen Output | 1208 |
| Efficacy | 126lm/w |
| Colour Temperature | 2400K |
| CRI | Ra≥90 |
| MacAdam Step | <3SDCM |
| Lifetime | L80 50,000Hrs |

| | |
|-----------------------|-----------------------------------|
| LEDs Per Meter | 80 led/m |
| Cutting Interval | 100mm |
| LED Pitch | 12.5mm |
| Height | 4.5mm |
| Width | 10mm |
| Max Run Length | 7m |
| Control Gear | On/Off/ Mains / 0-10 / DALI / DMX |
| IP Rating | IP65 |
| Operating Temperature | -20 to 50°C |
| Beam Angle | 120° |
| Classification | 3 |

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA