FUSION FLEX DYN 24W/M MINI 8 IP67

NGA/LL/HPM8/DYN/1/120120/24/21-65/67

LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A High Output, Dynamic White LED Strip with a sleek design for use in mini profiles. This dynamic strip offers tunable colour temperatures to create the ideal atmosphere in tight or detailed spaces.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.





















TECHNICAL INFORMATION

Product Code	NGA/LL/HPM8/DYN/1/120120/24/21- 65/67
Product Group	LED Strip
Power Consumption	24w/m
Supply Voltage	24V DC
Туре	Constant Voltage
Lumen Output	21K:821 65K:1160 MAX:2140
Efficacy	90lm/w
Colour Temperature	2100K - 6500K
CRI	Ra≥90
MacAdam Step	<3SDCM
Lifetime	50,000Hrs

LEDs Per Meter	120+120 led/m
Cutting Interval	50mm
LED Pitch	8.33mm
Height	4.5mm
Width	10mm
Max Run Length	5m
Control Gear	0-10 / DALI / DMX
IP Rating	IP67
Operating Temperature	-40 to 55°C
Beam Angle	120°
Classification	3



T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

