

# FUSION FLEX RGB 7.2W/M IP66

NGA/LL/RGB/1/30/7.2/66



LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A Low Output, RGB Colour LED Strip, designed to add a touch of colour and elegance to any setting.

## PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.



## TECHNICAL INFORMATION

Product Code	NGA/LL/RGB/1/30/7.2/66
Product Group	LED Strip
Power Consumption	7.2w/m
Supply Voltage	24V DC
Type	Constant Voltage
Lumen Output	R:75 G:170 B:35 MAX:280
Efficacy	39lm/w (MAX)
Colour Temperature	RGB
CRI	N/A
MacAdam Step	N/A
Lifetime	50,000Hrs

LEDs Per Meter	30 led/m
Cutting Interval	100mm
LED Pitch	33.33mm
Height	2.2mm
Width	10mm
Max Run Length	5m
Control Gear	0-10 / DALI / DMX
IP Rating	IP66
Operating Temperature	-40 to 55°C
Beam Angle	120°
Classification	3

### UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

### MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

# NGA