

# FUSION FLEX RGBW 19.2W/M 60LED/M IP66

NGA/LL/RGBW/1/60/19.2/W-3000/66




LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A Medium Output, Colour + White LED Strip, designed to add a blend of vivid colours and crisp white light to enhance any environment.

## PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.



## TECHNICAL INFORMATION

Product Code	NGA/LL/RGBW/1/60/19.2/W-3000/66
Product Group	LED Strip
Power Consumption	19.2w/m
Supply Voltage	24V DC
Type	Constant Voltage
Lumen Output	R:150 G:340 B:75 W:430 MAX:995
Efficacy	89lm/w (3000K)
Colour Temperature	RGBW(3000K)
CRI	Ra≥90
MacAdam Step	<3SDCM
Lifetime	50,000Hrs

LEDs Per Meter	60 led/m
Cutting Interval	100mm
LED Pitch	16.67mm
Height	2.2mm
Width	10mm
Max Run Length	5m
Control Gear	0-10 / DALI / DMX
IP Rating	IP66
Operating Temperature	-40 to 55°C
Beam Angle	120°
Classification	3

### UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

### MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

# NGA