FUSION FLEX ZEDLED 9.6W/M 6000K IP66

NGA/LL/ZL/1/9.6/6000/66 LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

A Low Output, Bendable LED Strip, designed for versatile installations where sharp angles and dynamic layouts are required. Its innovative structure allows it to bend left and right with ease, making it ideal for intricate designs, uneven surfaces, and creative lighting solutions.

PRODUCT NOTES

- For optimal thermal performance, pair this LED strip with a suitable aluminium heat sink.
- To achieve a more homogeneous light output, use a profile with greater depth than the LED pitch. NGA profiles are recommended for best results.
- Custom-cut fixtures are available upon request to meet specific project requirements.






















TECHNICAL INFORMATION

Product Code	NGA/LL/ZL/1/9.6/6000/66
Product Group	LED Strip
Power Consumption	9.6w/m
Supply Voltage	24V DC
Туре	Constant Voltage
Lumen Output	810
Efficacy	84lm/w
Colour Temperature	6000K
CRI	Ra≥90
MacAdam Step	<3SDCM
Lifetime	50,000Hrs

LEDs Per Meter	60 led/m
Cutting Interval	100mm
LED Pitch	16.67mm
Height	1.3mm
Width	6mm
Max Run Length	5m
Control Gear	On/Off/ Mains / 0-10 / DALI / DMX
IP Rating	IP66
Operating Temperature	-40 to 55°C
Beam Angle	120°
Classification	3



T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

