

FLEXCURVE SURFACE 2535

NGACS35




SPECIFICATION SHEET

PRODUCT DESCRIPTION

A surface-mounted or suspended inward curved aluminium profile designed for side-emitting light effects in architectural and commercial spaces. Its clean, minimalist form and customisable curvature support the creation of circular or freeform shapes. Ideal for applications requiring distinctive, perimeter-style illumination such as retail, offices, displays, and public interiors.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 60 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: New Opal 74%.



TECHNICAL INFORMATION

Product Code	NGACS35
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Side Emitting
Profile Material	Curved extruded aluminium
Profile Finish	Black / White / RAL
Diffuser Material	PMMA
Diffuser Options	New Opal

Profile Type	Curved (min Radius \geq 300 mm)
Dimensions	W 25mm x H 35mm
Weight	0.496 kg/m
Max Power	38.4W/m
Max Strip Width	26mm
Beam Angle	120°
IP Rating	IP20
Accessories	Aluminium end caps/ Suspension kit/ Joiners

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA