

FLEXLINE CORNER 3030 S

NGA3030S1

SPECIFICATION SHEET



PRODUCT DESCRIPTION

A surface-mounted corner aluminium profile designed for 45° LED presentation in wall-to-ceiling junctions. Its squared diffuser delivers even, directional illumination across adjacent surfaces, making it suitable for both ambient and accent lighting applications. The larger housing accommodates wider LED strips or higher outputs where required.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA3030S1
Product Group	Aluminium Profile
Installation Type	Corner
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 30 x H 30mm
Weight	0.29 kg/m
Max Power	15W/m
Max Strip Width	20mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic end caps/ Mounting clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA