

FLEXLINE PLASTER-IN 5315

NGA5315

SPECIFICATION SHEET



PRODUCT DESCRIPTION

A plaster-in aluminium profile designed for 45° outward corner installation on plasterboard edges and reveals. Its angled recessed structure allows for flush integration, delivering sharp lines of direct light along architectural forms. Ideal for enhancing corners in residential and commercial interiors with minimalist, built-in illumination.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA5315
Product Group	Aluminium Profile
Installation Type	Plaster-In
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 52.83 x H 15mm
Weight	0.43 kg/m
Max Power	15W/m
Max Strip Width	12mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic end caps

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA