

FLEXLINE RECESSED 2206

NGA2206

SPECIFICATION SHEET



PRODUCT DESCRIPTION

A recessed aluminium profile designed for flush integration into cabinetry, wall panels, or joinery. Its flanged edges conceal mounting grooves, delivering a clean trim detail with soft, uniform illumination. Ideal for residential and commercial interiors where discreet, low-profile linear lighting is required.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 240 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA2206
Product Group	Aluminium Profile
Installation Type	Recessed
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 21.7 x H 6.7mm
Weight	0.11 kg/m
Max Power	15W/m
Max Strip Width	11mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic end caps/ Metal mounting clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA