

# FLEXLINE RECESSED 3110

NGA3110

SPECIFICATION SHEET


## PRODUCT DESCRIPTION

A recessed aluminium profile designed for linear lighting in ceilings and joinery. The wide internal channel accommodates larger LED strips, while the curved diffuser helps reduce glare and soften the output. Ideal for architectural lighting applications where a clean, integrated finish is required.



## PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



## TECHNICAL INFORMATION

Product Code	NGA3110
Product Group	Aluminium Profile
Installation Type	Recessed
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 30.3 x H 9.75mm
Weight	0.185 kg/m
Max Power	20W/m
Max Strip Width	20mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic end caps/ Mounting clips

## UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

## MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA