

FLEXLINE RECESSED 6575

NGA6575




SPECIFICATION SHEET

PRODUCT DESCRIPTION

A recessed aluminium profile with angled internal reflectors to improve light distribution and reduce glare. The wide channel supports high-output LED strips, while the flanged trim conceals cut edges for a seamless finish. A lower compartment can be used to house an integrated driver or other components, supporting a streamlined installation.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA6575
Product Group	Aluminium Profile
Installation Type	Recessed
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 65 x H 74.7mm
Weight	1.653 kg/m
Max Power	30W/m
Max Strip Width	31mm
Beam Angle	120°
IP Rating	IP20
Accessories	Aluminium end caps/ Metal mounting clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA