

FLEXLINE RECESSED 7032

NGA7032




SPECIFICATION SHEET

PRODUCT DESCRIPTION

A recessed aluminium profile designed with an integrated heatsink base to support higher-output LED strips. Its flanged trim ensures a seamless fit into ceiling or wall surfaces, while the wide internal channel offers enhanced light distribution and improved thermal management. Ideal for architectural lighting in residential or commercial environments.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA7032
Product Group	Aluminium Profile
Installation Type	Recessed
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 70 x H 32mm
Weight	2.75 kg/m
Max Power	30W/m
Max Strip Width	39mm
Beam Angle	120°
IP Rating	IP20
Accessories	Aluminium end caps/ Spring clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA