

FLEXLINE RECESSED 9135

NGA9135



SPECIFICATION SHEET

PRODUCT DESCRIPTION

A recessed aluminium profile with angled internal reflectors to enhance beam control and reduce glare. The wide channel accommodates multiple runs of LED strip, while the flanged trim creates a seamless finish in plasterboard or joinery. Ideal for general, task, or display lighting.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 3 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA9135
Product Group	Aluminium Profile
Installation Type	Recessed
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 76 x H 35mm
Weight	1.26 kg/m
Max Power	30W/m
Max Strip Width	55mm
Beam Angle	120°
IP Rating	IP20
Accessories	Aluminium end caps/ Spring clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA