

FLEXLINE STEP 6026

NGA6026

SPECIFICATION SHEET



PRODUCT DESCRIPTION

A step-edge aluminium profile designed for stair lighting applications, featuring a 40° downward-facing beam for clear tread illumination. Its integrated anti-slip surface enhances safety while maintaining a clean, architectural appearance. Ideal for commercial and residential staircases where reliable, low-profile step lighting is required.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA6026
Product Group	Aluminium Profile
Installation Type	Step and Stair
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Clear

Profile Type	Straight
Dimensions	W 60mm x H 25.7mm
Weight	0.693 kg/m
Max Power	9.6W/m
Max Strip Width	5mm
Beam Angle	40°
IP Rating	IP20
Accessories	Plastic endcaps/ Plastic clips/ Metal clips/ Adjustable clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA