

FLEXLINE SURFACE 2019

NGA2019



SPECIFICATION SHEET

PRODUCT DESCRIPTION

A versatile aluminium LED profile suitable for both surface-mounted and suspended installations. Its design includes a back plate that conceals clips and cables, ensuring a clean and streamlined appearance. With a 120° beam angle, it provides wide, uniform illumination ideal for offices, hospitality settings, and retail environments.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 180 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, Frost 89%.



TECHNICAL INFORMATION

Product Code	NGA2019
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Opal / Frost

Profile Type	Straight
Dimensions	W 19.5mm x H 18.8mm
Weight	0.21 kg/m
Max Power	19.2W/m
Max Strip Width	15mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic endcaps/ Metal clips/ adjustable clips/ Suspension kit

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA