

# FLEXLINE SURFACE 2020 AT

NGA2020AT


SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A surface-mounted or suspended aluminium profile with a U-shaped diffuser extending beyond the housing for wide, uniform illumination. Suitable for offices, hospitality spaces, and retail interiors where clean, continuous light lines are desired.

## PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 180 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, Frost 89%.



## TECHNICAL INFORMATION

Product Code	NGA2020AT
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Opal / Frost

Profile Type	Straight
Dimensions	W 19.5mm x H 19.2mm
Weight	0.217 kg/m
Max Power	19.2W/m
Max Strip Width	15mm
Beam Angle	120°
IP Rating	IP20
Accessories	Plastic endcaps/ Metal clips/ adjustable clips/ Suspension kit

### UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

### MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA