

# FLEXLINE SURFACE 2833 IP67

NGA2833IP


SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A surface-mounted or suspended aluminium profile with an IP67 rating, designed for environments requiring moisture and dust resistance. Featuring an 80° beam angle, it provides focused, uniform illumination—ideal for lighting corners in cabinetry, closets, or behind furniture, and for accentuating displayed objects such as decorative items, plants, or food products.

## PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 180 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Clear 95%.



## TECHNICAL INFORMATION

Product Code	NGA2833IP
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Clear

Profile Type	Straight
Dimensions	W 28mm x H 33mm
Weight	0.942 kg/m
Max Power	14.4W/m
Max Strip Width	12mm
Beam Angle	80°
IP Rating	IP67
Accessories	Aluminium endcaps/ Aluminium Mounting plate/ Suspension Kit

## UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

## MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA