

# FLEXLINE SURFACE 2870

NGA2870



SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A surface-mounted aluminium profile featuring 60° up/down beam angles, designed for wall installations with dual-sided illumination. Its balanced design makes it ideal for decorative lighting in corridors, hospitality spaces, and architectural features.

## PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 240 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, Milky 75%, Frost 89%, Clear 95%.



## TECHNICAL INFORMATION

Product Code	NGA2870
Product Group	Aluminium Profile
Installation Type	Surface
Light Distribution	Indirect / Wall-wash
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA / PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 27.7mm x H 70mm
Weight	0.666 kg/m
Max Power	14.4W/m
Max Strip Width	12mm
Beam Angle	60°(up)/60°(down)
IP Rating	IP20
Accessories	Aluminium endcaps/ Metal clips

## UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

## MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA