

FLEXLINE SURFACE 3538 WS

NGA3538WS

SPECIFICATION SHEET


PRODUCT DESCRIPTION

A surface-mounted or suspended aluminium profile featuring a 60° beam angle and a recessed diffuser for controlled, low-glare illumination. Ideal for comfortable, seamless lighting in residential, retail, office, and hospitality interiors, it can also be assembled into custom shapes using 180°, 90°, or 120° joiners.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 60 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: New Opal 74%.



TECHNICAL INFORMATION

Product Code	NGA3538WS
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	New Opal

Profile Type	Straight
Dimensions	W 35mm x H 37.5mm
Weight	0.658 kg/m
Max Power	38.4W/m
Max Strip Width	22.6mm
Beam Angle	60°
IP Rating	IP20
Accessories	Aluminium endcaps/ Metal clips/ Wall clips/ Suspension kit/ Joiners

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA