

# FLEXLINE SURFACE 3538

NGA3538WN




SPECIFICATION SHEET

## PRODUCT DESCRIPTION

A surface-mounted or suspended aluminium profile featuring a 60° beam angle and a flush diffuser for clean, directional lighting. It can be assembled into custom shapes using 180°, 90°, or 120° joiners, making it ideal for flexible architectural and commercial installations.

## PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 60 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, New Opal 74%, Frost 89%, Clear 95%.



## TECHNICAL INFORMATION

Product Code	NGA3538WN
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Opal / New Opal / Frost / Clear

Profile Type	Straight
Dimensions	W 35mm x H 37.5mm
Weight	0.676 kg/m
Max Power	38.4W/m
Max Strip Width	30mm
Beam Angle	60°
IP Rating	IP20
Accessories	Aluminium endcaps/ Metal clips/ Wall clips/ Suspension kit/ Joiners

## UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

## MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA