


FLEXLINE SURFACE 3558

NGA3558

SPECIFICATION SHEET



PRODUCT DESCRIPTION

A surface-mounted or suspended aluminium profile featuring a 60° beam angle and an extended U-shaped diffuser that creates a more prominent visual profile. It can be assembled into custom shapes using 180°, 90°, or 120° joiners, making it ideal for bold architectural and commercial lighting designs.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 60 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%.



TECHNICAL INFORMATION

Product Code	NGA3558
Product Group	Aluminium Profile
Installation Type	Surface or Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Opal

Profile Type	Straight
Dimensions	W 35mm x H 57.5mm
Weight	0.741 kg/m
Max Power	38.4W/m
Max Strip Width	30mm
Beam Angle	60°
IP Rating	IP20
Accessories	Aluminium endcaps/ Metal clips/ Wall clips/ Suspension kit/ Joiners

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA