

FLEXLINE SURFACE 4916

NGA4916

SPECIFICATION SHEET


PRODUCT DESCRIPTION

A surface-mounted aluminium profile designed for double-sided wall washing. It features opposing LED channels that project light in both directions across the mounting surface, creating a balanced indirect lighting effect. Ideal for decorative or ambient lighting in corridors, stairwells, or feature walls.



PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Milky 65–70%, Opal 75%, Frost 85–90%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA4916
Product Group	Aluminium Profile
Installation Type	Surface
Light Distribution	Indirect / Wall-wash
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 17.3 x H 49mm
Weight	0.35 kg/m
Max Power	15W/m (x2)
Max Strip Width	12mm
Beam Angle	120°
IP Rating	IP20
Accessories	Aluminium end caps/ Metal mounting clips

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA