

FLEXLINE SUSPENDED Ø75

NGA75




SPECIFICATION SHEET

PRODUCT DESCRIPTION

A suspended aluminium profile designed to deliver full 360° illumination. Its cylindrical body houses a central LED tray for even light distribution, making it ideal for decorative pendant lighting in retail, hospitality, or modern architectural spaces.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%.



TECHNICAL INFORMATION

Product Code	NGA75
Product Group	Aluminium Profile
Installation Type	Suspended
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal

Profile Type	Straight
Dimensions	Ø 75mm
Weight	0.643 kg/m
Max Power	42W/m
Max Strip Width	10mm
Beam Angle	360°
IP Rating	IP20
Accessories	Plastic endcaps/ Suspension kit

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA