

FLEXLINE TRIMLESS 5048

NGA5048T




SPECIFICATION SHEET

PRODUCT DESCRIPTION

A trimless recessed aluminium profile featuring a 60° beam angle and a flush diffuser for clean, directional lighting. Designed for seamless integration into plasterboard ceilings, it can be assembled into custom shapes using 180°, 90°, or 120° joiners—ideal for architectural and commercial lighting applications requiring a minimalist, continuous finish.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 60 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 2 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%, Milky 75%, Frost 89%, Clear 95%.



TECHNICAL INFORMATION

Product Code	NGA5048T
Product Group	Aluminium Profile
Installation Type	Plaster-In
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PMMA
Diffuser Options	Opal / Milky / Frost / Clear

Profile Type	Straight
Dimensions	W 50mm x H 48mm
Weight	1.442 kg/m
Max Power	28.8W/m
Max Strip Width	30mm
Beam Angle	60°
IP Rating	IP20
Accessories	Aluminium endcaps/ Spring clips/ L bracketss/ Aluminium bridge base

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA