

FLEXLINE WALKOVER 2625 IP67

NGA2625W



SPECIFICATION SHEET

PRODUCT DESCRIPTION

A recessed aluminium profile with IP67 protection, designed for walk-over use in exterior and wet environments. Its durable construction and 40° beam angle make it ideal for outdoor landscape applications, including pavements, bike lanes, driveways, and parking areas—perfect for marker lighting between paving stones or along pathways.

PRODUCT NOTES

- When selecting an LED strip for this profile, we recommend a minimum LED density of 120 LEDs/m to achieve homogeneous, dot-free illumination, depending on diffuser type.
- A minimum of 1 LED strip runs per metre is recommended to ensure uniform light distribution and eliminate shadowing.
- Diffuser light transmittance: Opal 63%.



TECHNICAL INFORMATION

Product Code	NGA2625W
Product Group	Aluminium Profile
Installation Type	Walkover
Light Distribution	Direct
Profile Material	6063-T5 Anodised Aluminium
Profile Finish	Silver / Black / White / Custom
Diffuser Material	PC
Diffuser Options	Opal

Profile Type	Straight
Dimensions	W 26mm x H 25mm
Weight	0.85 kg/m
Max Power	19.2W/m
Max Strip Width	12mm
Beam Angle	40°
IP Rating	IP67
Accessories	Plastic endcaps

UK & EUROPE HQ

T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ

T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA